



FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.

1300 I STREET, N. W.
WASHINGTON, DC 20005-3315

202 • 408 • 4000
FACSIMILE 202 • 408 • 4400

WRITER'S DIRECT DIAL NUMBER:

ATLANTA
404 • 653 • 6400
PALO ALTO
650 • 849 • 6600

TOKYO
011 • 813 • 3431 • 6943
BRUSSELS
011 • 322 • 646 • 0353

June 04, 1998

ATTORNEY DOCKET NO. 04931.0039

BOX PATENT APPLICATION

Assistant Commissioner for Patents
Washington, D.C. 20231

New U.S. Patent Application

Title: DISCHARGE SPACE STRUCTURE OF PLASMA DISPLAY PANEL
AND METHOD OF FABRICATING ITS BARRIER

Inventor: Myung-Ho PARK

Address: #20 Yoido-dong, Youngdungpo-gu, Seoul, Korea

Sir:

We enclose the following papers for filing in the United States Patent and Trademark Office in connection with the above patent application.

1. Application - 13 pages, including 3 independent claims and 15 claims total.
2. Drawings - 7 sheets of formal drawings containing 11 figures.
3. Certified copy of Korean Application Nos. 1997/23358 and 1997/23359 both filed June 5, 1997.

This application is being filed under the provisions of 37 C.F.R. 1.53(f). Applicant awaits notification from the Patent and Trademark Office of the time set for filing the Declaration and paying the filing fee of \$790.00. Please do not charge the filing fee to our Deposit Account without our authorization.

The Commissioner is hereby authorized to charge any other fees due under 37 C.F.R. § 1.16 or § 1.17 during the pendency of this application to our Deposit Account No. 06-0916.

FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.

Applicant claims the right to priority based on Korean Application Nos. 1997/23358 and 1997/23359 both filed June 5, 1997.

Please accord this application a serial number and filing date.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,
GARRETT & DUNNER, L.L.P.

By



Ernest F. Chapman
Reg. No. 25,961

04931.0039/mld
Enclosures

04931.0039/mld

UNITED STATES PATENT APPLICATION

by

Myung-Ho PARK

For

**DISCHARGE SPACE STRUCTURE OF PLASMA DISPLAY
PANEL AND METHOD OF FABRICATING ITS BARRIER**

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N.W.
WASHINGTON, DC 20005
202-408-4000

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a plasma display panel (referred to hereinafter as PDP) and, more particularly, to a discharge space structure of a PDP and method of fabricating its barrier, in which the center of each discharge space formed by barriers has a height different from that of the boundary between discharge spaces adjacent to each other, to prevent undesirable discharge from occurring in neighboring cells when address discharge between a sustain electrode and address electrode is carried out.

Discussion of Related Art

Fig. 1 shows a structure of a conventional three-electrode plane discharge PDP.

Referring to Fig. 1, the PDP is composed of the front substrate 1 for displaying pictures and back substrate 2 arranged in parallel with the front substrate 1, having a specific distance from each other. The front substrate 1 has a plurality of sustain electrode lines 6 in a certain interval, a dielectric layer 8 formed on a plurality of sustain electrode lines 6 to restrict discharge current, and a protective layer 9 formed on dielectric layer 8 to protect sustain electrode lines 6. The back substrate 2 has a plurality of barriers 3 for forming a plurality of discharge spaces, a plurality of address electrode lines 4 formed between barriers 3, perpendicular to sustain electrode lines 6, and a fluorescent layer 5 formed on both sides of barriers 3 so as to cover address electrode lines 4, to emit a visible ray during discharge.

Fig. 2 is a cross-sectional view showing the combination of the front and back substrates of Fig. 1. A process of displaying a picture using cells in the conventional PDP constructed as above is explained below. First of all, when a preliminary discharge voltage is applied to corresponding sustain electrode lines 6, preliminary discharge occurs between sustain electrode lines 6 to allow the following address discharge to occur stably. When an address discharge voltage is supplied to the sustain electrode line 6 and corresponding address electrode line 4, address discharge is carried out between them. That is, an electric field is created inside the cell to accelerate electrons in a discharge gas, and neutral particles in the gas collide with the accelerated electrons to be ionized into electrons and ions. The neutral particles' collision with the ionized electrons is repeated so that the neutral particles are ionized into electrons and ions rapidly. By doing so, the discharge gas is transformed into a plasma state, and simultaneously vacuum ultraviolet rays are generated.

The vacuum ultraviolet rays excite fluorescent layer 5, to generate a visible ray. When this visible ray is externally emitted through front substrate 1, radiation of a cell, and thereby display of a picture, can be externally recognized. Thereafter, when a sustain discharge voltage of above 150V is supplied to corresponding sustain electrode lines 6, sustain discharge occurs between them, maintaining radiation of each cell for a certain period of time.

A process of forming discharge space in the conventional PDP is described below with reference to Figs. 2 and 3. First of all, address electrodes 4 are formed on back substrate 2, and barriers 3 for preventing undesirable discharge from generating in neighboring discharge regions are formed between address electrodes 4. Front and back substrates 1 and 2 are combined using frit glass (not shown). A discharge gas is put into the discharge space formed inside the

combined substrates, and then the combined substrates are sealed. Barrier 3 is conventionally formed in such a manner that a dielectric layer is formed and multi level printed in a certain pattern using a screen mask. The height of barrier 3 is conventionally approximately 100 to 150 μm . To obtain this height, it is required that the dielectric layer is sequentially laminated ten times and printed, and the minimum width of such a barrier is about 50 to 60 μm .

There is another method of forming the barrier, in which a barrier material is coated on the entire surface of the substrate, a mask layer is formed, and the barrier material layer is etched to form the barrier. The etching may be carried out through wet etching method using an etchant and dry etching method using an abrasive. A method of forming the barrier through the dry etching which is also called sand blast is explained below with reference to Fig. 4. Address electrodes 4 are formed on back substrate 2, a barrier material 10 is coated on the substrate including address electrodes 4 by 50 to 80 μm and dried, and a dry film 11 is laminated thereon. Dry film 11 is exposed by ultraviolet rays, covered with a mask, and developed to form a pattern. Then, barrier material layer 10 is etched by sand blast using the pattern as a mask, to form a barrier shape 10. The etching is carried out in such a manner that the barrier material layer is etched in an exfoliating solution for 100 to 300 sec, cleaned, and fired in a furnace at 200 to 500 $^{\circ}\text{C}$ for 20 to 60 min, thereby forming barriers 10. After the formation of barriers 10, dry film 11 is removed and the fluorescent layer is printed between the barriers.

In the conventional discharge space structure fabricated through the above-described process, all the centers of the discharge spaces and the boundary between neighboring discharge spaces have approximately the same height, as shown in Fig. 3. That is, the barriers and address electrodes are formed in parallel with each other. Accordingly, plasma can be easily diffused

between cells which vertically lie adjacent to each other, and thus visible rays generated by the fluorescent layer intrude into each other in the same stripe during ultraviolet rays discharge, creating color spread. This deteriorates color purity.

SUMMARY OF THE INVENTION

5 Accordingly, the present invention is directed to a discharge space structure of a PDP and method of fabricating its barrier that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

10 An object of the present invention is to provide a discharge space structure of a PDP and method of fabricating its barrier, in which the center region of each discharge space formed by barriers has the height different from that of the boundary region between discharge spaces adjacent to each other, so as to prevent undesirable discharge from occurring in neighboring cells, to remove color spread in the same stripe during address discharge between a sustain electrode and an address electrode, and to effectively use a generated visible ray.

15 To accomplish the object of the present invention, there is provided a discharge space structure of a plasma display panel including first and second substrates opposite each other, a barrier layer formed on the first substrate and having a plurality of raised portions, and a plurality of discharge spaces, each space being formed between the barrier layer and the second substrate, and being at least partially defined by at least two adjacent raised portions of the barrier layer.

20 A method of making the barrier layer of the plasma display device includes coating a barrier material layer on a substrate, forming a photosensitive layer on the barrier material layer, exposing the photosensitive layer to light through a mask, the mask having a pattern

Fig. 7 is a view showing a mask employed for forming the barrier according to the present invention; and

Figs. 8A and 8B show discharge space structures according to another embodiment of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

The discharge space structure according to the present invention is described below with reference to Fig. 5. As shown in Fig. 5, a PDP of the present invention is constructed in such a manner that the front substrate 101 and back substrate 102 are combined, a dielectric layer 108 is formed on sustain electrodes 106 arranged on the front substrate 101, a protective layer 109 is formed on dielectric layer 108, address electrodes 104 are arranged on the back substrate 102, barriers 103 are formed between address electrodes 104, and a fluorescent layer 105 is formed on the inner walls of barriers 103. A discharge space P formed by fluorescent layer 105 which is formed between barriers 103 and has a hemispheric shape. Fluorescent layer 105 is formed with a certain height at boundary A between cells in the same stripe and its height is gradually reduced from boundary A to the center of each cell. Though fluorescent layer 105 is formed in a hemispherical shape in this embodiment, fluorescent layer 105 and sides of barrier 103 can have any shapes if discharge space P is formed in a shape similar to a plasma formation shape.

A method of forming the barrier to obtain the discharge space structure shown in Fig. 5 is explained below with reference to Figs. 6A, 6B and 6C. Referring to Fig. 6A, a barrier material

103 is coated on back substrate 102 on which the electrodes are formed. Referring to Fig. 6B, photoresist 112 is coated on barrier material layer 103, and exposure is performed to the back substrate on which barrier material layer 103 is coated using a mask shown in Fig. 7. Referring to Fig. 6C, the barrier material layer is developed and etched, to form barrier 103. The mask used for the exposure process has a horizontal pattern 110 for exposing the barrier, and a vertical pattern 111 for forming boundary region A between neighboring cells in the same stripe, which is perpendicular to the horizontal patterns.

The operation of the PDP according to the present invention is explained below. When voltage of above 100V is applied between electrodes of the front and back substrates to drive the display panel, ultraviolet ray discharge is generated between a couple of sustain electrode 106 and address electrode 104. When a visible ray is emitted from R,G,B fluorescent materials of fluorescent layer 105 while the plasma forming region P of the discharge space is as shown in Fig. 5, this visible ray is not diffused into neighboring cells in the same stripe but emitted to the front of the panel.

Figs. 8A and 8B show discharge space structures according to another embodiment of the present invention. Fig. 8A shows that the portion of fluorescent layer 105 corresponding to each discharge space has a semi-elliptical shape and Fig. 8B shows that a certain area of the center of fluorescent layer 105 is flat. As described above, according to the present invention, color spread due to diffusion of visible ray between cells is prevented, resulting in improvement in luminance of the PDP.

It will be apparent to those skilled in the art that various modifications and variations can be made in the discharge space structure of a PDP and method of fabricating its barrier of the

0 **0** **0** **0** **0**

5

a barrier layer formed on the first substrate and having a plurality of raised portions; and

a plurality of discharge spaces, each space being formed between the barrier layer and the second substrate, and being at least partially defined by at least two adjacent raised portions of the barrier layer.

10

4. The discharge space structure as claimed in claim 2, wherein a portion of the fluorescent layer is flat.

15

6. The discharge space structure as claimed in claim 2, wherein the portion of the fluorescent layer corresponding to each discharge space has a semi-elliptical shape.

7. The discharge space structure as claimed in claim 2, wherein the discharge space defined by the fluorescent layer has a plasma formation shape.

8. The discharge space structure as claimed in claim 1, wherein the barrier layer is formed in a plasma formation shape.

9. The discharge space structure as claimed in claim 1, wherein a height of the barrier layer decreases from a boundary between two discharge spaces to the centers of said spaces.

10. The discharge space structure as claimed in claim 1, wherein the discharge spaces are spherical.

11. The discharge space structure as claimed in claim 7, wherein the plasma formation shape is spherical.

12. A discharge space structure of a plasma display panel, comprising:
a substrate;
a pair of barriers formed on the substrate; and

a plurality of discharge spaces, each space being formed between said pair of barriers, each barrier having a plurality of raised portions, said raised portion defining a boundary between two adjacent discharge spaces.

13. The discharge space structure as claimed in claim 12, further comprising:

5 a fluorescent layer formed on each barrier, and having a plurality of raised portions corresponding to the raised barrier portions, each fluorescent layer raised portion defining a boundary between adjacent discharge spaces between the barriers.

14. A method of making a barrier layer of a plasma display device, comprising:

coating a barrier material layer on a substrate;

10 forming a photosensitive layer on the barrier material layer;

exposing the photosensitive layer to light through a mask, said mask having a pattern corresponding to cells of the plasma display device; and

etching the barrier material layer to form said plurality of cells.

15 15. The method as claimed in claim 14, wherein the mask has a horizontal pattern for defining a barrier and a vertical pattern for defining a boundary between two adjacent cells.

Abstract of Disclosure

A discharge space structure of a plasma display panel is provided in which rays generated by a cell are not diffused into neighboring cells but sent to the front of the panel, to prevent color spread in the same stripe, improving luminance of the plasma display panel. The plasma display panel is constructed in such a manner that the front and back substrates, parallel to each other, are combined using frit glass, a dielectric layer is formed on display electrodes arranged on the front substrate, a protective layer formed on the dielectric layer, address electrodes are arranged on the back substrate, barriers are formed between the address electrodes, and a fluorescent layer is formed between the barriers, in which each discharge space defined by the fluorescent layer is formed in a hemispheric shape, to send rays generated by the fluorescent layer to the front of the panel.

6640307 90405050

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N.W.
WASHINGTON, DC 20005
202-408-4000

FIG. 1

PRIOR ART




FIG. 2

PRIOR ART






FIG. 3

PRIOR ART




864090" 90409090

FIG. 5




364090" 30406060

FIG. 6A



coating photoresist

FIG. 6B



exposing / developing

etching solution

FIG. 6C



FIG. 7




FIG. 8A






FIG. 8B



United States Patent & Trademark Office

Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

- 1 Application papers are not suitable for scanning and are not in compliance with 37 CFR . 52 because:
- ☐ All sheets must be the same size and either A4 (21 cm x 29.7 cm) or 8-1/2"x 11"
Pages _____ do not meet these requirements.
 - ☐ Papers are not flexible, strong, smooth, non-shiny, durable, and white.
 - ☐ Papers are not typewritten or mechanically printed in permanent ink on one side.
 - ☐ Papers contain improper margins. Each sheet must have a left margin of at least 2.5 cm (1") and top, bottom and right margins of at least 2.0 cm (3/4").
 - ☐ Papers contain hand lettering.
2. Drawings are not in compliance and were not scanned because:
- ☐ The drawings or copy of drawings are not suitable for electronic reproduction.
 - ☐ All drawings sheets are not the same size. Pages must be either A4 (21 cm x 29.7 cm) or 8-1/2" x 11"
 - ☐ Each sheet must include a top and left margin of at least 2.5 cm (1"), a right margin of at least 1.5 cm (9/16") and a bottom margin of at least 1.0 cm (3/8").
3. Page(s) _____ are not of sufficient clarity, contrast and quality for electronic reproduction.
- 4 Page(s) _____ are missing.
- 5 OTHER No Declaration Enclosed